



# WAREHOUSE MATRIX

A.B.N 29 764 742 043

PO Box 24  
Balaklava SA 5461

Telephone 08 8862 2078  
Facsimile 08 8862 2033

## TECHNICAL INFORMATION

### SEALED TIMBER OR PARQUETRY FLOOR POLISHING

The polishing of the surface of sealed timber or parquetry floors to prevent ingress of dirt and water based stains.

### EQUIPMENT

Either, poly cotton mop and roller bucket, or tray and lambs-wool applicator.  
Recommended Floor Sealer Finish  
Hand and feet protection

### METHOD - ENSURE ADEQUATE VENTILATION

1. Thoroughly clean the surface and remove all traces of dirt, wax and acrylic accumulation. The use of a stripping emulsion to thoroughly clean the floor is recommended.
2. Ensure the floor to be sealed is dry.
3. Apply a first coat of recommended Floor Sealer Finish in a thin even coat with a clean cotton mop or lambs-wool applicator to the floor, avoid leaving pools and do not allow traffic on the floor until surface is dry.
4. Cover the applicator or mop in their containers with a cloth dampened with water between sealer finish applications.
5. After allowing sufficient time for the first coat to thoroughly dry, apply 2 more coats of recommended Floor Sealer Finish, allowing sufficient drying time between coats.

**PROVIDE REGULAR MAINTENANCE**, by using a recommended Neutral Floor Cleaning system and wet or damp mop procedures in conjunction with machine scrubbing and buffing.



Main Office: 27 Gwy Terrace, Balaklava SA 5461  
Email: [info@warehousematrix.com.au](mailto:info@warehousematrix.com.au)