



WAREHOUSE MATRIX

A.B.N 29 764 742 043

PO Box 24
Balaklava SA 5461

Telephone 08 8862 2078
Facsimile 08 8862 2033

TECHNICAL INFORMATION

SHEET or VINYL TILE FLOOR SEALING

The sealing of the surface of sheet or vinyl tile floor coverings to prevent ingress of dirt and water based stains.

EQUIPMENT

Either, poly cotton mop and roller bucket, or tray and lambswool applicator.
Recommended Basecoat sealer
Recommended Topcoat finish
Hand protection

METHOD - ENSURE ADEQUATE VENTILATION

1. Thoroughly clean the floor surface and remove all traces of dirt, wax and acrylic accumulation. The use of a stripping emulsion to thoroughly clean the floor is recommended.
2. Ensure the floor to be sealed is dry.
3. Buff the floor with a blue or red floor pad to seal the surface of the vinyl in preparation to receive a coat of floor sealer finish.
4. Apply a basecoat of Recommended Floor Seal in a thin even coat with a clean cotton or lambswool applicator to the floor, avoid leaving pools and do not allow traffic on the floor until the surface is dry.
5. **The applicator should be washed with water immediately after use.**
6. Under normal conditions, one coat is sufficient to adequately seal the surface.
On old or very porous floors a second coat may be desirable.
7. After allowing sufficient time for the basecoat seal or seals to dry, apply 2 or 3 topcoats of Recommended Floor Sealer Finish, allowing sufficient drying time between coats.

PROVIDE REGULAR MAINTENANCE, by using an approved Neutral Floor Cleaner OR Residual Floor Cleaner and damp mop procedures in conjunction with high speed machine buffing.



Main Office: 27 Gwy Terrace, Balaklava SA 5461
Email: info@warehousematrix.com.au